

C1XR IP Cabin Camera		
Product		Main Features
		● 1920*1080@25fps Resolution ● PON(DC12V) power input interface ● With infrared Led light - 8-10 meters of infrared consumption range ● Multiple optional Lens -support 2.8mm、4mm ● Application Scenario: ● Support three kinds of stream ● Support N9M protocol.
Specification		
Product Model	953C1XR	
Sensor	1/2.9"2MP CMOS	
Resolution	1920(H)x1080(V)	
Minimum Illumination	0.1Lux (Color) ,0Lux(Infrared)	
Electronic Shutter	1/30 Second - 1/10000Second	
Back-Light Compensation	Support	
S/N	≥48dB	
Infrared Range IR	8~10m	
Lens	2.8mm,4mm M12, Fixed Aperture F2.0	
FOV	2.8mm=H*V98° 51°	
	4mm= H*V 76°41°	
Video Compression Standard	H.264、 H.265 Default H264	
Compression Output Rate	512Kbps-8Mbps	
Image Resolution	Main Stream:1080P(or 720p) @ 25fps	
	Sub Stream:VGA/D1/CIF Default @10FPS	
	Net Transmission Stream: Default @10FPS	
CBR/VBR	Support Default VBR	
Network Port	10M/100M Adjustable Ethernet Port	
Network Protocol	TCP/IP、 HTTP、 DHCP、 NTP、 FTP	
N9M	Support	
Client Preview	Built-In WEB Server, Support IE Browser	
Installation	Installed at the In-Car Ceiling	
Operation Temperature	-40°C-- +70°C	
Operation Humidity	0% - 90%	
Power Supply	PON (DC9-16V)	
Waterproof Class	N/A	
Power Consumption	PON<2w (Day) <3w (Night);	
Dimension(Unit in mm)	93MM(L)x93MM(W)x78MM(H)	
Dimension(Unit in mm)		

